

TRITON[®] MAX



Triton Max has been engineered and built to withstand demanding Med-Tech environments and 24/7 usage. With a carbon steel frame, metal-to-metal assembly and the ability to support up to a 500lb weight capacity, Triton Max delivers reliable performance day after day.

SPECIFICATIONS

FEATURES

- 23" extra-wide contoured molded seat with waterfall edge ensures 24-hour comfort
- Dynamic range of adjustments support the full range of seated postures from active forward-leaning to recline
- **NEW!** High performance sure-lock flat black footring with 23.5" diameter (on stool heights)
- Supports up to 500 lbs
- 15-Year, Three-Shift Warranty
- TritonMax has SCS Indoor Advantage Gold Certification and may help contribute toward LEED certification
- All metal construction

CONSTRUCTION



- 28" die-cast aluminum base
- 14-gauge steel seat pan
- 16-gauge pressed steel inner back plate with a 18-gauge outer shell
- Integrated steel arm structure with metal-to-metal connections eliminates points of failure
- High resiliency flame-retardant 3.25" thick seat foam with a density of 2.4 lbs. per cubic foot
- Class 4 pneumatic cylinder: 1.12" diameter with a 17-4 taper top end for maximum strength
- Heat-bonded powder coat finish

OPTIONS

- Arms: an adjustable arm option (height range of 6"-10" above seat, inside width range of 20.5"-23"); or a fully articulating arm option w/ slide (adds 3 locking pivot positions, and 2.5" of travel front to back)
- Casters: multi-surface dual wheel is standard. A variety of other casters are also available
- 23.5" flat black footring is standard. Flat surface chrome (mid and high heights only) or fixed 18" rounded chrome (desk height only) also available
- Desk, mid, **NEW!** desk-to-counter, high, and extended range heights
- Upholstered outer back
- Extra large back (desk height only)
- 28" polished aluminum base
- TB 133 Fire Code
- Class 100 Cleanroom
- ESD, or CR/ESD Combination

DIMENSIONS

| MODEL# | MAXIMUM OVERALL DIMENSIONS | | SEAT DIMENSIONS | | SEAT HEIGHT FROM FLOOR WHEN SEATED E | BACK DIMENSIONS | | WEIGHT LBS. |
|-----------|----------------------------|-------|-----------------|-------|---|-----------------|-------|----------------|
| | A | B | C | D | | F | G | |
| TMLD4 - 7 | 42.00 | 29.50 | 23.00 | 20.00 | 16.50 - 21.75 | 18.00 | 18.00 | 61 |
| TMLM4 | 49.50 | 29.50 | 23.00 | 20.00 | 22.00 - 29.50 | 18.00 | 18.00 | 66 |
| TMLH4 | 54.50 | 29.50 | 23.00 | 20.00 | 24.00 - 34.25 | 18.00 | 18.00 | 67 |
| TMXD4 - 7 | 48.50 | 29.50 | 23.00 | 20.00 | 16.50 - 21.75 | 22.00 | 24.75 | 64 |



Dimensions listed in inches.
Adding arms will increase weight by 10 lbs.

Measurements are for standard mechanisms and can vary +/- .5".
Seat slider and arm options can increase overall height and seat height .25" -1"