# FUSION® ROUND STOOL **FUSION® ROUND STOOL R+**







The Fusion Round Stool offers a wider arc of movement, still with flexible ease and comfort. This model is versatile and is also available in our R+™ technology.

## **SPECIFICATIONS**

## **FEATURES**

- · Three seat heights
- · Contoured foam seat ensures 24-hour comfort
- Hand or foot-activated height adjustment, accessible from any direction
- High performance twist-lock footring with 20" diameter (on hand-activated stool heights)
- Supports up to 300 lbs
- 10-Year, Three-Shift Warranty
- · Available with back
- SCS Indoor Advantage Gold Certification and may help contribute toward LEED certification
- ISO Class 5 Cleanroom (Fed Std 209 Class 100)

## **CONSTRUCTION**

- 16-gauge steel seat pan
- 25" fiberglass-reinforced nylon base (hand-activated); 24.75" die-cast painted aluminum base (foot-activated)
- High resiliency 2.5" thick seat foam with a density of 2.4 lbs. per cubic foot
- Class 4 pneumatic cylinder
- · Heat-bonded powder coat finish

#### **DIMENSIONS**


#### **OPTIONS**


- Casters: multi-surface dual wheel is standard. A variety of other casters are also available
- High-performance twist-lock footrings: flat black is standard. Flat surface chrome is also available. Footrings are only available on hand-activated high-height stools
- Desk, desk-to-counter, and high heights
- Textile or vinyl upholstery also available with R+ Technology



- Patented Rhino Plus combination of polyurethane and molded foam provides a comfortable seat
- Resists punctures, tears and virtually all spills; and cleans easily with bleach or ethanol
- Textured surface prevents slipping
- R+ properties: tear strength of 17.7 kgF, puncture resistance of 9.9 kgF, stretch of 660%, abrasion resistance of 25,000 and a Ross Flex rating of 150,000 flexes

MODEL#		EL#	MAXIMUM OVERALL DIMENSIONS A B		SEAT DIMENSIONS C	SEAT HEIGHT FROM FLOOR WHEN SEATED D	BACK DIMENSIONS E F		WEIGHT LBS.
	RP0D1	RS0D1	20.75	24.00	16.00	15.50 - 20.75			18
	RP0F1	RS0F1	22.25	23.00	16.00	17.25 - 22.25			19
	RP0G1	RS0G1	28.50	23.00	16.00	21.25 - 28.50			20
	RP0H1	RS0H1	32.75	24.00	16.00	22.75 - 32.75			23
	RPBD2	RSBD2	37.00	24.00	16.00	16.25 - 21.50	17.00	12.00	26
	RPBH2	RSBH2	48.50	24.00	16.00	23.50 - 33.50	17.00	12.00	31





Dimensions listed in inches